

Completion of this form, and providing us with highlighted drawings, has proven to greatly reduce our turn-around time on quotation requests. **Your assistance is greatly appreciated.**

Request Date: \_\_\_\_\_

Quotation Due Date: \_\_\_\_\_

Company Name: \_\_\_\_\_

Contact Name: \_\_\_\_\_

Email: \_\_\_\_\_


Phone: \_\_\_\_\_

Project Name: \_\_\_\_\_

Project Location: \_\_\_\_\_

Specifier: \_\_\_\_\_

Date Req'd on Site: \_\_\_\_\_



PanelGrip® Standard



PanelGrip® Narrow

Approx. Footage: \_\_\_\_\_

Glass Thickness Range:

Shoe Length:  10ft  20ft

.496" - .550"

PanelGrip® Style:  Standard  Narrow

.569" - .638"

Glass Type:  Monolithic  Laminate

.624" - .726"

Pre-drilled Countersunk Holes:  Yes  No

.719" - .781"

Mounting Surface:  Steel  Concrete

.768" - .874"

ICC-ES Compliant:  Yes  No

Cladding:  Yes  No      Length:  10ft

Type:  Satin Aluminum  Black Aluminum  Satin Stainless  
 Satin Anodized Aluminum  Polished Stainless

End Caps:  Yes  No      Number of End Caps: \_\_\_\_\_

Gasket:  With Cladding  Without Cladding

Cap Rail:  304 Stainless Steel Slotted  316 Stainless Steel Slotted  
 304 Stainless Steel Oval Formed  Extruded Aluminum, 900 lb/ft  
 304 Stainless Steel Roll Formed  Brass Roll Formed

Finish Type:  Mill  Satin  Longitudinal Satin  
 Polished  Satin Anodized (Aluminum rail only)



If ICC-ES compliance needed, please contact rfq@mailwagner.com.

<b>Isolators</b> Choose one matching shoe	<b>Aluminum Extruded Shoe</b> Choose one, follow column down		<input type="checkbox"/> GR2460HCB <input type="checkbox"/> GR2460HCB-10	<input type="checkbox"/> GR2457HCB <input type="checkbox"/> GR2457HCB-10	
	1/2" Monolithic .469" to .531"	<input type="checkbox"/>	PG2460 Brown Isolator White .090" Pad	<input type="checkbox"/> PG2472 Black Isolator Black .160" Pad	
	9/16" Laminate .496" to .550"	<input type="checkbox"/>	PG2460 Brown Isolator White .090" Pad	<input type="checkbox"/> PG2472 Black Isolator Black .160" Pad	
	15mm Laminate .569" to .638"	<input type="checkbox"/>	N/A	<input type="checkbox"/> PG2415 Dk. Grey Isolator White .090"/.125" Pad	
	17mm Laminate .642" to .726"	<input type="checkbox"/>	N/A	<input type="checkbox"/> PG2417 Lt. Grey Isolator White .090"/.125" Pad	
	3/4" Monolithic .719" to .781"	<input type="checkbox"/>	N/A	<input type="checkbox"/> PG2475 White Isolator White .090"/.125" Pad	
<b>Mounting Hardware</b> Choose one matching shoe	Concrete	Self-Tapping Anchor	<input type="checkbox"/> WB7216 3/8" by 4"	<input type="checkbox"/> KHEZ500-0450 1/2" by 4 1/2"	
		Expansion Anchor	<input type="checkbox"/> 3/8" by 4" *	<input type="checkbox"/> HSL3M1040 1/2" by 5 1/8"	
	Steel (1/2" min)	Zinc Plated Steel Cap Screw	<input type="checkbox"/> SHC1Z3816-0750 3/8"-16 by 3/4"	<input type="checkbox"/> SHC1Z1213-0750 1/2"-13 by 3/4"	
		Stainless Steel Cap Screw	<input type="checkbox"/> SHC1Z3816-0750 3/8"-16 by 3/4"	<input type="checkbox"/> SHC1Z1213-0750 1/2"-13 by 3/4"	
	<b>End Caps</b> Choose one matching shoe	With Cladding	Stain Aluminum	<input type="checkbox"/> GR2852EC.4	<input type="checkbox"/> GR2876EC.4
			Satin Anodized Al	<input type="checkbox"/> GR2852EC.4AN	<input type="checkbox"/> GR2876EC.4AN
Stain Stainless			<input type="checkbox"/> GR3852EC.4	<input type="checkbox"/> GR3876EC.4	
Without Cladding		Polished Stainless	<input type="checkbox"/> GR3852EC.7	<input type="checkbox"/> GR3876EC.7	
		Stain Aluminum	<input type="checkbox"/> GR2852E.4	<input type="checkbox"/> GR2876E.4	
		Satin Anodized Al	<input type="checkbox"/> GR2852E.4AN	<input type="checkbox"/> N/A	
	Stain Stainless	<input type="checkbox"/> GR3852E.4	<input type="checkbox"/> GR3876E.4		
	Polished Stainless	<input type="checkbox"/> GR3852E.7	<input type="checkbox"/> GR3876E.7		

\*Recommended to purchase through Hilti

<b>Aluminum Extruded Shoe</b>		<input type="checkbox"/>	GR2460HCB	<input type="checkbox"/>	GR2457HCB
Choose one, follow column down			GR2460HCB-10		GR2457HCB-10
<b>Cladding</b> Choose one	Anodized Aluminum	<input type="checkbox"/>	GR2802.4AN	<input type="checkbox"/>	GR2802.4AN
	Satin Stainless Steel	<input type="checkbox"/>	GR3802.4	<input type="checkbox"/>	GR3802.4
	Polished Stainless Steel	<input type="checkbox"/>	GR3802.7	<input type="checkbox"/>	GR3802.7
	Tape	<input type="checkbox"/>	GR975	<input type="checkbox"/>	GR975

<b>Works With Both Shoes</b>		With Cladding		Without Cladding	
<b>Gaskets</b> Choose one	20' Length Cap Rail GR9397-20	<input type="checkbox"/>	GR9302-20	<input type="checkbox"/>	GR9355-20
	40' Length Cap Rail GR9397-40	<input type="checkbox"/>	GR9302-40	<input type="checkbox"/>	GR9355-40
	100' Length Cap Rail GR9397-100	<input type="checkbox"/>	GR9302-100	<input type="checkbox"/>	GR9355-100
	250' Length Cap Rail GR9397	<input type="checkbox"/>	N/A	<input type="checkbox"/>	GR9355
	500' Length Cap Rail N/A	<input type="checkbox"/>	GR9302	<input type="checkbox"/>	N/A