

Completion of this form, and providing us with highlighted drawings, has proven to greatly reduce our turnaround time on quotation requests. **Your assistance is greatly appreciated.**

Request Date: _____

Quotation Due Date: _____

Company Name: _____

Contact Name: _____

Email: _____


Phone: _____

Project Name: _____

Project Location: _____

Specifier: _____

Date Req'd on Site: _____



Level Lock PlusTM
Shoe



Level Lock PlusTM
Mechanisms



Cladding



Alignment Pins

Approx. Footage: _____

Shoe Length: 10ft 20ft 5ft Mitered Corner

Glass Type: Monolithic Laminate

Pre-Drilled Countersunk Holes: Yes No


Mounting Surface: Steel Concrete

Glass Thickness Range:

.469" - .550" Monolithic
12-14mm Laminated

.569" - .726" Monolithic
15-17mm Laminated

.705" - .906" Monolithic
19-21mm Laminated



Cap Rail: 304 Stainless Steel Slotted 316 Stainless Steel Slotted
 304 Stainless Steel Oval Formed Extruded Aluminum
 304 Stainless Steel Roll Formed Brass Roll Formed

Finish Type: Mill Satin Longitudinal Satin

For Cladding

Polished Satin Anodized (Aluminum rail only)

 @wagnercompanies



LEVEL LOCK PLUS™ HOW TO BUY SKU

*SKU includes mechanisms, shoe and alignment tabs

Glass Thickness		.469" - .550" / 13mm LL1213	.569" - .726" / 15-17mm LL5817	.705" - .906" / 19-21mm LL3421
Choose one, follow column down				
Glass Shoe	10' Lengths, 12" Conter Bored Holes	<input type="checkbox"/> LL1213KIT10*	<input type="checkbox"/> LL5817KIT10*	<input type="checkbox"/> LL3421KIT10*
	10' Lengths, 8" Counter Bored Holes	<input type="checkbox"/> LL1213.8KIT10*	<input type="checkbox"/> LL5817.8KIT10*	<input type="checkbox"/> LL3421.8KIT10*
	20' Lengths, 12" Counter Bored Holes	<input type="checkbox"/> LL1213KIT20*	<input type="checkbox"/> LL5817KIT20*	<input type="checkbox"/> LL3421KIT20*
	20' Lengths, 8" Counter Bored Holes	<input type="checkbox"/> LL1213.8KIT20*	<input type="checkbox"/> LL5817.8KIT20*	<input type="checkbox"/> LL3421.8KIT20*
	5' Lengths, Mitered Corners, 12" Counter Bored Holes	<input type="checkbox"/> LL1213KITMK*	<input type="checkbox"/> LL5817KITMK*	<input type="checkbox"/> LL3421KITMK*
	5' Lengths, Mitered Corners, 8" Counter Bored Holes	<input type="checkbox"/> LL1213.8KITMK*	<input type="checkbox"/> LL5817.8KITMK*	<input type="checkbox"/> LL3421.8KITMK*
Optional Add-Ons Cladding	Clear Satin Anodized Aluminum	<input type="checkbox"/> GR2802.4AN	<input type="checkbox"/> GR2802.4AN	<input type="checkbox"/> GR2802.4AN
	Satin Stainless Type 304	<input type="checkbox"/> GR3802.4	<input type="checkbox"/> GR3802.4	<input type="checkbox"/> GR3802.4
	Satin Stainless Type 316	<input type="checkbox"/> GR3806.4	<input type="checkbox"/> GR3806.4	<input type="checkbox"/> GR3806.4
	Polished Stainless Type 304	<input type="checkbox"/> GR3802.7	<input type="checkbox"/> GR3802.7	<input type="checkbox"/> GR3802.7
Optional Add-Ons End Caps for use with Cladding and Cladding Tape	Satin Aluminum 2.625" by 4.125"	<input type="checkbox"/> GR2852EC.4	<input type="checkbox"/> GR2852EC.4	<input type="checkbox"/> GR2852EC.4
	Satin Aluminum 2.875" by 4.125"	<input type="checkbox"/> GR2876EC.4	<input type="checkbox"/> GR2876EC.4	<input type="checkbox"/> GR2876EC.4
	Satin Anodized Aluminum 2.625" by 4.125"	<input type="checkbox"/> GR2852EC.4AN	<input type="checkbox"/> GR2852EC.4AN	<input type="checkbox"/> GR2852EC.4AN
	Satin Anodized Aluminum 2.875" by 4.125"	<input type="checkbox"/> GR2876EC.4AN	<input type="checkbox"/> GR2876EC.4AN	<input type="checkbox"/> GR2876EC.4AN
	Satin Stainless 2.625" by 4.125"	<input type="checkbox"/> GR3852EC.4	<input type="checkbox"/> GR3852EC.4	<input type="checkbox"/> GR3852EC.4
	Satin Stainless 2.875" by 4.125"	<input type="checkbox"/> GR3876EC.4	<input type="checkbox"/> GR3876EC.4	<input type="checkbox"/> GR3876EC.4
	Polished Stainless 2.625" by 4.125"	<input type="checkbox"/> GR3852EC.7	<input type="checkbox"/> GR3852EC.7	<input type="checkbox"/> GR3852EC.7
	Polished Stainless 2.875" by 4.125"	<input type="checkbox"/> GR3876EC.7	<input type="checkbox"/> GR3876EC.7	<input type="checkbox"/> GR3876EC.7

Additional options on the next page.

Glass Thickness		.469" - .550" / 13-14mm LL1213	.569" - .726" / 15-17mm LL5817	.705" - .906" / 19-21mm LL3421
Choose one, follow column down				
Optional Add-Ons End Caps for use with Cladding and Silicone	Satin Aluminum 2.625" by 4.125"	<input type="checkbox"/> GR2852E.4	<input type="checkbox"/> GR2852E.4	<input type="checkbox"/> GR2852E.4
	Satin Aluminum 2.75" by 4.125"	<input type="checkbox"/> GR2876E.4	<input type="checkbox"/> GR2876E.4	<input type="checkbox"/> GR2876E.4
	Satin Anodized Aluminum 2.625" by 4.125"	<input type="checkbox"/> GR2852E.4AN	<input type="checkbox"/> GR2852E.4AN	<input type="checkbox"/> GR2852E.4AN
	Satin Stainless 2.625" by 4.125"	<input type="checkbox"/> GR3852E.4	<input type="checkbox"/> GR3852E.4	<input type="checkbox"/> GR3852E.4
	Satin Stainless 2.75" by 4.125"	<input type="checkbox"/> GR3876E.4	<input type="checkbox"/> GR3876E.4	<input type="checkbox"/> GR3876E.4
	Polished Stainless 2.625" by 4.125"	<input type="checkbox"/> GR3852E.7	<input type="checkbox"/> GR3852E.7	<input type="checkbox"/> GR3852E.7
	Polished Stainless 2.75" by 4.125"	<input type="checkbox"/> GR3876E.7	<input type="checkbox"/> GR3876E.7	<input type="checkbox"/> GR3876E.7
Optional Add-Ons Gaskets	Without Cladding, 250 ft.	<input type="checkbox"/> GR9LL1056	<input type="checkbox"/> GR9LL1056	<input type="checkbox"/> GR9LL1056
	Without Cladding, 50 ft.	<input type="checkbox"/> GR9LL1056-40	<input type="checkbox"/> GR9LL1056-40	<input type="checkbox"/> GR9LL1056-40
	Without Cladding, 25 ft.	<input type="checkbox"/> GR9LL1056-20	<input type="checkbox"/> GR9LL1056-20	<input type="checkbox"/> GR9LL1056-20
	Shoe Isolator, 10 pack	<input type="checkbox"/> GR9LL1250	<input type="checkbox"/> GR9LL1250	<input type="checkbox"/> GR9LL1250