



LUMENLINEAR™ SYMMETRIC

Another Lumenrail®
Component for Life
Safety and Light

©2018 Wayne Cable

LINEAR LUMINAIRE

Our linear product is a state-of-the-art, low-voltage LED light fixture that provides exceptional lighting performance to enhance any stairway, ramp or walkway application. Its soft light provides ample illumination for safety and ambiance without the glare or harshness of overhead lighting. Available with warm, neutral or cool white color temperatures, and a range of solid color options for static hues. Standard low, mid and high output offerings make Lumenlinear a highly flexible and practical solution for adding beauty and light to your life safety installations.



Specifications subject to change without notice. Verify data at time of order.

- Industry leading output:
60° and 120° symmetric beam spreads
- Matte and transparent lens options
- Available in: 152, 284 or 413 lpf
(4000 K Values)
- IES full cutoff classification when installed in
Wagner Architectural Systems handrail
- Fully gasketed, extruded aluminum housing
- ETL wet location listed, UL1598 certified
- 5 year warranty
- Cast 316 stainless steel, mechanical
mounting, secure, but easily serviceable
- CCT standard in 5 white options
- 4 solid color options
- Up to 88 CRI standard, 95+ available upon
request
- 9 standard lengths from 6" to 54"

LUMENLINEAR™ SYMMETRIC

Another Lumenrail® Component
for Life Safety and Light

PROJECT NAME: _____

REP AGENCY: _____

APPROX. LINEAR FT: _____

SERVICE OPTIONS: Field Measure Job Site Support System Installation



SCAN QR CODE
for technical information,
downloads and instructions.


PART NUMBER BUILDER

LULS30K40120TS-18 EXAMPLE	LULS						
	FIXTURE TYPE	COLOR TEMP	FIXTURE WATTAGE	BEAM ANGLE	LENS OPTION	LENGTH	
	LULS- Lumenlinear™	27K- 2700 K 30K- 3000 K 35K- 3500 K 40K- 4000 K 50K- 5000 K	BLU- Blue GRN- Green RED- Red AMB- Amber	20- 1.85 W/FT 40- 3.57 W/FT 60- 5.45 W/FT	70- 70° Spread 120- 120° Spread	TS- Transparent Symmetric MS- Matte Symmetric	6- 7.64" 36- 37.14" 12- 13.51" 42- 43.07" 18- 19.39" 48- 48.95" 24- 25.33" 54- 54.89" 30- 31.23"

ELECTRICAL SPECIFICATIONS


 <i>All electrical connections to be made by a qualified electrician in accordance with all national, state and local electrical codes.</i>	24VDC	ETL LISTED WET, UL 1598/CSA 22.2	0-10V INPUT (PWM)	-40°F TO +120°F
	INPUT VOLTAGE	CERTIFICATIONS	DIMMING	OPERATING TEMP
	CLASS 2 REQUIRED	5 YEARS	UP TO 77 LM/W LED	UP TO 88 (95+ AVAIL. UPON REQUEST)
	DRIVER	WARRANTY	EFFICIENCY	CRI

CONSTRUCTION



An extruded aluminum housing and fully gasketed assembly insure heat dissipation and ingress protection to IP67. Stainless steel hardware and mechanical attachment promote easy installation and longevity.

PHOTOMETRICS



The symmetric output can be specified in narrow 70° or industry leading wide 120° beam spreads. Installed in Wagner Lumenrail®, Lumenlinear achieves full IES cutoff. Reports to view or download are available by scanning the QR code or visiting our website.

LUMENGEAR™ LED DRIVER & NEMA ENCLOSURE OPTIONS

Wagner offers multiple ETL listed options for both 24VDC power supplies and NEMA enclosures. Quantities and types will be configured based on your specifications and design. Additional specification options are available by request. Not all options apply to all products, please verify compatibility with the factory.

- CLASS II DRIVERS:**
- STD 100W
 - Dali, DMX, 0-10V Dimming Protocols
 - Multiple Wattages
 - Made in USA Units Available

NEMA ENCLOSURES:
4X - Polycarbonate, Painted Steel or Stainless Steel

LUMENPOST™:
Integrated 100W, 0-10V DIM

Specifications subject to change without notice. Verify data at time of order.

@wagnercompanies



888-243-6914 // rfq@mailwagner.com
10600 West Brown Deer Road // Milwaukee, WI 53224, USA

© 2021 R&B Wagner, Inc. All Rights Reserved.
WagnerCompanies.com
LULS SUBM R5